

**Statement of Evidence:**

**C023**

East Quarter Corner of Section 2, Township 38 North, Range 30 West, Graham Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office set a wood post at this location and bearing trees were recorded:

3" Blk Oak	S 9 E	34 links
3" Blk Oak	S 85 W	22 links

1908 County Surveyor's Record Book 2, page 162, shows a survey of Section 2 by M.J. Cleveland notes a distance of 40.90 chains (2699.40 feet) to the NE corner Sec. 2 and a distance of 40.79 chains (2692.14 feet) to the SE corner Sec. 2. He established the corner by lost method at proportionate measurement.

1990 Paul Wellen, LS 10461, found a 1" X 24" Iron Pin at the intersection of a fence line west and the northerly extension of County Road 41. He replaced the iron pin with a cast iron monument and filed a Certificate of Location (Doc. No. 199551). His notes also show he found the iron in 1988 with distances of 2691.20 feet to the NE corner of Section 2 and 2686.92 feet to the SE corner of Section 2, which is the lost position. Other record shows his distances as 2682.04 feet to the SE corner and 2688.75 feet to the NE corner.

2008 Westwood Professional Services, Inc. found a CIM at the corner location fitting 1990 Wellen ties. Measured 2691.26 feet to the NE corner and 2686.93 feet to the SE corner of Section 2. CIM is accepted as marking the obliterated position for this corner.

County Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N-193829.625  
E-504864.872