

Statement of Evidence:

C121

North Quarter Corner of Section 12, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post and bearing trees were recorded.

6" Blk Oak	S 59 E	5 links
6" Aspen	N 44 W	5 links

1939 County Engineer's Notebook No. 128 contains survey of CAR 22 running east to west on section line. No corner is shown with a distance of 5338.3 feet between section corners.

1964 County Engineer's Notebook No. 276 contains a road survey for CSAH No. 22 running west to east on section line. No corner is shown with a POT set on fence line north with stationing giving distances of 2671.6 feet to the NW corner and 2667.5 feet to the NE corner.

1988 Bruce Skipton, LS 17768, dug with a backhoe and found a stone down 2 feet at the intersection of a road east/west and an occupation line north. He set a cast iron monument over it and filed a Certificate of Location (#191338). He notes a distance of 2672.29 feet to the NW Cor Sec 12 and a distance of 2666.70 feet to the NE Cor Sec 12.

2003 Westwood Professional Services, Inc. found CIM and measured 2672.42 feet to the Northwest corner and 2666.70 to the Northeast corner.
Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 191198.974
E- 507662.443

2008 Westwood Professional Services, Inc. found CIM fitting 1988 Skipton and our 2003 distances to the NE and NW corners of Section 12. CIM is accepted as marking the obliterated position for this corner. County Coordinates Obtained by GPS coincide with 2003 position.