

**Statement of Evidence:**

**F093**

East Quarter Corner of Section 9, Township 37 North, Range 31 West, Watab Township,  
4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

- 1850 Original US General Land Office survey set a wood post in a mound with a pit for the corner location.
- 1972 Certificate of Survey, filed as Doc. No. 132159, M. W. Carley, LS 855, set corner lost with 2660.51 feet to section corners.
- 1981 Reference ties to 1 1/2 " x 30" iron pipe, 4" below surface, 2 feet east of center of north-south road:  
4" Twin Pine West 90.70  
6" Pine WSW 43.79  
5" Pine SW 83.45
- 1982 David Regan, LS 12236, found a 1 1/2 " pipe, 2 feet east of the centerline of a north/south township road and on a fence line west. He replaced the iron with a cast iron monument and filed a Certificate of Location (#162597). Same ties as 1981.
- 1987 This corner is noted on the following:  
*SURVEYORS CERTIFICATE FOR EDWARD WEILSON dated 12/18/1987* by William Lunser, LS 9394.
- 2004 MN/DOT  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-156097.729  
E-462823.470
- 2008 Westwood Professional Services, Inc. found a CIM 2 feet east of the centerline of 15<sup>th</sup> Ave NW. No ties from Certificate of Location #162597 were found at the time of survey. CIM measures 2660.96 feet to the NE corner and 2660.17 feet to the SE corner of Section 9 and fits a fence line to the west. CIM is accepted as marking the obliterated position for this location. Coordinates obtained by GPS coincide with 2004 MN/DOT position.