

Statement of Evidence:

E121

The North Quarter Corner of Section 12, Township 38 North, Range 32 West, West Langola Township, 4th Principal Meridian, Benton County, Minnesota.

- 1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.
- | | | |
|-------------|------------|-----------|
| 20" Bur Oak | N 86 1/2 E | 483 links |
| 8" Bur Oak | N 65 1/2 E | 336 links |
- 1978 Paul Wellen, LS 10461, found a 1/2" iron pipe on the centerline of an east/west road and a tree line to the south. He notes a distance of 2745.64 feet to the NE corner of Section 12.
- 1988 Bruce Skipton, LS 17768, found a 1" iron pipe and set a cast iron monument over it and filed a Certificate of Location (#191343).
- 2001 Westwood Professional Services, Inc. found a cast iron monument down 1.5'.
- 2003 Westwood Professional Services, Inc. located a cast iron monument using GPS. Corner is 330 feet, +/-, east of TH 10. MN/DOT alignment and right of way map has no information on this corner.
County Coordinates Obtained by GPS (Cast Iron Monument)
NAD 83 (1996 Adjustment)
N-190882.004
E-443418.171
- 2008 Westwood Professional Services, Inc. found a CIM at the corner location. CIM fits longstanding occupation along the north/south quarter line of Section 12. CIM is accepted as marking the obliterated corner position. County Coordinates Obtained by GPS coincide with 2003 position.