

Statement of Evidence:

A073

The East Quarter Corner of Section 7, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

5" Tamarack N 32 E 18 links
5" Tamarack N 69 1/2 W 17 links

1933 County Engineer's notebook No. 68 for SAR 6 shows hub at corner with ties:

F.P. W 27.0'
F.P. NW 33.8'

Stationing gives distance of 2650.6 feet to the SE corner and 2655.1 feet to the NE corner with no angle. Notes show fence line east and west.

1953 County Engineer's Notebook No. 196 contains a road survey for SAR 6 running from south to north on section line. Corner is shown marked as a spike set for POT in center of road with fence lines east and west. Same ties as 1954 below. Stationing gives distance of 2652.2 feet to the SE corner and 2655.6 feet to the NE corner

2000 David Regan, LS 12236, set an I.P. on centerline of north-south road and a fence line east.

2001 On September 20, 2001 Westwood Professional Services, Inc. found a 1/2" iron pipe capped RLS #12236 at the centerline of Township Road 67 (running north and south). Removed the pipe and set a cast iron monument and established reference ties. Measured 2650.59 to SE corner and 2657.20 feet to NE corner of Section 7.

County Coordinates
NAD 83 (1996 Adjustment)
N-
E-