

Statement of Evidence:

A123

East Quarter Corner of Section 12, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

8" Sugar	N 52 W	40 links
10" Birch	S 70 E	16 links
6" Birch	South	18.29 chains
10" Birch	North	15.40 chains

1996 Corner was established by John Oliver, LS 8194, Mille Lacs County Surveyor. He set a cast iron monument. His statement of evidence refers to Mille Lacs County Surveyor records in 1912 and 1918 from which he based the corner position. For details see his Certificate of Location filed as Doc. No. 244636. County Coordinates from John Oliver & Associates by traverse NAD 83 (1986 Adjustment)
N- 188128.504
E- 573239.987

2002 No resurvey information was found on this corner in the Benton County records.

2008 Westwood Professional Services, Inc. found a CIM fitting 1996 Oliver ties. CIM fits on a straight line between the NE and SE corners of Section 12. Measured 2641.24 feet to the NE corner and 2649.03 feet to the SE corner. After analysis of the statement of evidence from Oliver's certificate, I agree with his method of perpetuating this corner. CIM is accepted as marking the obliterated position for this corner.

County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 188129.056
E- 573239.380