

**Statement of Evidence:**

**A133**

East Quarter Corner of Section 13, Township 38 North, Range 28 West, Granite Ledge Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

8" Basswood S 27 W 22 links  
6" Sugar N 52 E 22 links

No Date County Surveyor's Record Book 2, page 334, (Old) lists new BT's:

6" W. Oak N 54 1/2 E 96 links  
14" W. Pine S 40 E 65 links

1996 John Oliver, LS 8194, Mille Lacs County Surveyor, set corner at single proportion distance based on Judicial Road survey. He set a 3/4 " iron pipe and filed Certificate of Location (Doc. No. 244638). See his statement of evidence for details.

County Coordinates from John Oliver & Associates by traverse  
NAD 83 (1986 Adjustment)  
N- 182829.885  
E- 573368.521

2001 Dennis Pederson, LS 16095, used iron pipe as set by Oliver for survey in Section 13. He measured 2651.17 feet to the SE corner and 2651.12 feet to the NE corner of Section 13.

2008 Westwood Professional Services, Inc. found a 3/4" iron pipe fitting 1996 Oliver ties. Measured 2651.19 feet to the NE corner and 2651.40 feet to the SE corner. 3/4" iron pipe is accepted as marking the obliterated position for this corner.

County Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N- 182830.478  
E- 573367.426