

Statement of Evidence:

A193

East Quarter Corner of Section 19, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

9" Bur Oak	N 14 W	35 links
10" Blk Ash	N 50 E	22 links

1933 County Engineer's notebook No. 68 for SAR 6 does not show this corner, but shows a POT being 2642.5 feet from the SE corner and 2631.7 feet from the NE corner.

1953 County Engineer's Notebook No. 196 contains a road survey for SAR 6 running from south to north on section line. No corner is shown with stationing distance of 5274.7 feet for the east line of Section 19.

2002 No resurvey information was found on this corner in the Benton County records.

2004 Found ½" iron pipe with cap No. 23682 (Linda Brown) in center of County road. Measured 2636.76 feet to the NE corner and 2636.68 feet to the SE corner. Appears pipe was set at the lost position.
County Coordinates obtained by GPS to ½" iron pipe:
NAD 83 (1996 Adjustment)
N- 177400.699
E- 547189.747

2009 The Benton County Surveyor's Office found the iron pipe capped 23682 and excavated and found stones at the northeast and southeast corners of Section 19. The resulting measurements are 2632.38 feet to the north and 2636.68 feet to the south, falling south of the 1933 proportionate by 3.2 feet and falling 1.6 feet north of the lost position. The projection of a fence near the center of section 19 through a point on the east-west fence at the approximate CE1/16 hits the found iron. The split of the distance north at the north sixteenth falls 2.5 feet south of a fence to the east. Since the found iron capped 23682 fits the lost positions either by GLO or 1933 and falls on the occupation line west and fits a split at the north sixteenth, it is accepted as marking the obliterated corner position. The 2004 coordinates were verified