

**Statement of Evidence:**

**A243**

East Quarter Corner of Section 24, Township 38 North, Range 28 West, Granite Ledge Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office surveyor, Oscar F. Davis, set a wood post at this location and bearing trees were recorded.

10" Sugar	S 57 1/2 W	25 links
6" Blk Ash	S 84 E	23 links

No Date County Surveyor's Record Book 2, page 356, notes the following ties:  
Red Bldr 7 ft E/W and 3 ft high in CL N 47 1/2 E 'X' on rock 170 links

1912 Mille Lacs County: Deputy County Surveyor, S.L. Kennedy, resurveyed Sec 8-38-27. He notes a wood stake in a bog at Gov't and Judicial road corner.

1996 John Oliver, LS and Mille Lacs County Surveyor placed a 3/4" X 14" pipe at the corner location based on Kennedy's distance from the SE corner in center of north-south road and filed a Certificate of Location (#244640). Corner agrees with fence line east.

County Coordinates from John Oliver & Associates by traverse  
NAD 83 (1986 Adjustment)

N- 177545.964  
E- 573529.603

Information gives distances of 2645.90 feet to the SE corner and 2635.35 feet to the NE corner.

2003 Westwood Professional Services, Inc. found a 3/4" iron pipe agreeing with 1996 Oliver ties and distances to the NE and SE corners of Section 24. Iron pipe is accepted as marking the obliterated position for this corner.

County Coordinates Obtained by GPS to iron pipe:

NAD 83 (1996 Adjustment)  
N- 177546.437  
E- 573528.770