

Statement of Evidence:

L263

East Quarter Corner of Section 26, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at the corner location and bearing trees were recorded.

8" Tamarack	S 74 E	27 links
10" Blk Ash	N 80 W	20 links

1902 County Surveyor's Record Book 2, page 358, and Record Book A, Map No. 37, contains survey of Section 25 by John Whilt. Corner is shown at 39.63 1/2 chains (2615.91 feet) to the NE and SE corners Sec 26.

1937 County Engineer's Notebook No. 82 contains a road survey for SAR No. 9 running south to north. Notes show corner marked by a spike with town road west. Ties:

FP	NW	31.95'
FP	SW	26.45'

Stationing gives distances of 2621.7 feet to the SE corner and 2626.7 feet to the NE corner with no delta angle.

1962 County Engineer's Notebook No. 269 contains a road survey for CSAH No. 9 running south to north. Notes show corner marked by an iron in center of road as a POT with town road west. Same ties as listed below noted for 1969. Stationing gives distances of 2623.0 feet to the SE corner and 2626.7 feet to the NE corner.

1962 County Surveyor's Record Book 2, page 360, lists ties to an iron:

PP	NE	57.25'
Guy P	E	47.2'
PP	NW	57.8'

(Same ties noted in 1969 and 1972)

County Coordinates
NAD 83 (1996 Adjustment)
N-
E-