

Statement of Evidence:

A273

East Quarter Corner of Section 27, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land office survey set a wood post at this location and bearing trees were recorded.

8" Blk Oak N 87 E 21 links
10" Elm N 68 1/2 W 24 links

No Date County Surveyor's Record Book 2, page 362 notes a stone at the corner location.

1915 County Surveyor's Record Book 2, pages 362 and 363 and Record Book A, Map No. 13 notes in May 1915, J.P. Soderstrum found the old tamarack post, which was set by Whilt from Gov't B.T.'s. Testimony notes the corner is in the same place as when set in 1899. He notes a distance of 38.87 chains (2565.42 feet) to the NE Cor Sec 27 (stone). He then set a stone with an "X" at the location. He also notes a reference tie of larger boulder with an "X" marked W.C. N 89 E 440.

2002 On 10/17/02 Westwood Professional Services, Inc. dug with a backhoe and found a 10" x 10" x 18" pointed stone with an + on top down 1.5 feet. We measured 2570.40 feet to the NE corner of Section 27 (stone set by Soderstrum), which compared well to Soderstrum's distance. On October 24, 2002 Westwood Professional Services, Inc. set a cast iron monument over the stone and established reference ties. Certificate filed as Doc. No. 293732.

County Coordinates obtained by GPS to CIM

NAD 83 (1996 Adjustment)

N-172285.601

E-562981.857