

Statement of Evidence:

A293

The East Quarter Corner of Section 29, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

9" Maple	S 84 E	30 links
8" Ironwood	N 66 W	12 links

1930 County Engineer's notebook No. 56 contains a road survey by H. G. Elletson for CAR No. 27. Notes show road survey run south to north along section line. Ties:

F.P.	E	32.9'
F. P.	SE	38.3'

Stationing gives distances of 2611.0 feet to the SE corner and 2600.0 feet to the NE corner with a deflection angle of 0-34' right.

1962 County Surveyor's Records Book 2, page 366 shows an iron pipe with the following reference ties:

F.P.	E	32.8
F.P.	NE	62.9
T.P.	NW	82.2
P.P.	SE	54.3

2000 Westwood Professional Services, Inc. found a 3/4 " iron pin down 2 feet in north-south road and set a 1/2 " iron pipe over.

2001 Westwood Professional Services, Inc. found a 1/2" open iron monument over a 1" solid pin at the intersection of the centerlines of Township Road 67 (running north and south) and 130th Street NE (running from the west). We also checked for ties and found 1 tie that fit from 1962 (PP SE 54.22). We removed the 1/2" open iron monument and placed a cast iron monument over the 1" solid pin at the location of the corner and established reference ties. Measured 2610.79 feet to the SE corner and 2596.56 feet to the NE corner of Section 29.

2002 Certificate of Location filed as Doc. No. 291179.

2004 County Coordinates obtained by GPS to CIM:

NAD 83 (1996 Adjustment)
N- 172256.691
E- 552504.889