

Statement of Evidence:

A303

East Quarter Corner of Section 30, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

9" W Birch	S 29 W	25 links
12" W Birch	S 64 E	7 links

1933 County Engineer's notebook No. 68 for SAR 6 shows iron at corner with ties:

F.P.	SE	42.4'
F.P.	SW	45.5'

Stationing gives distance of 2565.4 feet to the SE corner and 2513.0 feet to the NE corner with a delta angle of 1-37' right. Notes show town road east and west.

1953 County Engineer's Notebook No. 196 contains a road survey for SAR 6 running from south to north on section line. Corner is shown marked by an iron in center of road with town road east and west. Same ties as 1954 and 1955 below.

Stationing gives distance of 2565.9 feet to the SE corner and 2513.1 feet to the NE corner.

1954 County Surveyor's Record Book 2, page 368 contains ties to an iron:

6" Poplar	SW	100.3
15" Elm stump	SW	188.0
TP	SE	105.9

County Highway plans show corner at PI 213+23.0 with delta 1-37' Rt.

1955 Ties:

TP	NE	70.3
PP	NW	56.0
PP	SW	78.6

1988 County Highway plans show corner assumed at PI 622+79.23 with a delta 1-36-40 Rt.

2001 Westwood Professional Services, Inc. found a RR spike at centerline of roads north-south and east-west.

2004 Measured 2516.13 feet to the NE corner and 2564.99 feet to the SE corner.

County Coordinates obtained by GPS to RR spike:

NAD 83 (1996 Adjustment)
N- 172248.059
E- 547230.654