

Statement of Evidence:

A313

East Quarter Corner of Section 31, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Blk Ash	S 50 E	42 links
6" Blk Ash	N 14 1/2 W	8 links

1933 County Engineer's notebook No. 68 for SAR 6 shows hub at corner with ties:

F.P.	E	20.8'
F.P.	NE	24.8'

Stationing gives distance of 2622.3 feet to the SE corner and 2626.2 feet to the NE corner with a delta angle of 0-13' right. Notes show fence line east.

1953 County Engineer's Notebook No. 196 contains a road survey for SAR 6 running from south to north on section line. Corner is shown marked by a hub set in center of road with fence west. Stationing gives distances of 2622.5 feet to the SE corner and 2627.3 feet to the NE corner with a delta angle of 0-14' right. Ties to corner 10 feet north of centerline of town road east:

6" Elm	NE	93.1
8" Ash	E	64.45

Plans show corner at PI 161+29.8. Fence west at 161+27, fence east at 161+43, and road east at 161+20.

2001 Westwood Professional Services, Inc. set a RR spike at centerline of road north-south and road west.

2004 Measured 2622.66 to the NE corner and 2624.50 feet to the SE corner.

County Coordinates obtained by GPS to RR spike.

NAD 83 (1996 Adjustment)

N- 167062.069

E- 547305.220