

Statement of Evidence:

A363

East Quarter Corner of Section 36, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

8" Tamarack	S 5 E	145 links
8" Y. Birch	N 2 W	119 links
A line tree 26" Pine South 16.42 chains		

Note Date: County Surveyor's Record Book 2, page 380, lists the following new bearing tree.

14" W. Oak stump	S 19 E	250 links
------------------	--------	-----------

1996 John Oliver, LS 8194, Mille Lacs County Surveyor, restored this corner at SPM and placed a 3/4" iron pipe at the centerline of 195th Avenue NE (running north and south) and +/-5 feet south of fence line extended from the west. He did not excavate here because there were no post GLO records and the corner location falls in a low area and would have most likely been removed by sub-cutting during construction. A Certificate of Location was filed (#244644).

County Coordinates from John Oliver & Associates by traverse:

NAD 83 (1986 Adjustment)
N- 166967.780
E- 573495.936

Information gives distances of 2634.23 feet to the section corners.

2001 On October 10, 2001 Westwood Professional Services, Inc. found an iron monument capped RLS #8194. We left monument as found and established reference ties.

2002 County Coordinates by GPS to Iron Pipe:

NAD 83 (1996 Adjustment)
N- 166968.240
E- 573495.660