

Statement of Evidence

A011

North Quarter Corner of Section 1, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set corner marked by a wood post with bearing trees noted as.

8" Sugar	N 25 E	8 links
8" Sugar	S 37 W	47 links

1919 Nels Peterson, Morrison County Surveyor, notes he set a concrete monument at all government corners along the south line of Lakin Township in Morrison County.

1994 On April 5, 1994, Kevin Festler, LS 22702, found a concrete monument with iron re-bar in the center. He prepared a Certificate of Location. He notes he accepted the corner found as the one set in 1919 by Peterson.

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:

N- 196003.900
E- 570434.830

2004 Dan Kron, LS 42621, reported using corner for survey in Section 1.

2012 The Benton County Surveyor's Office found a concrete monument with rebar as described by Nels Peterson in 1919. The found monument falls 3 feet west and 1.5 feet south of the lost position between a granite monument at the northeast corner of Section 1 and concrete monument at the northeast corner of Section 2. The concrete monument is accepted as marking the corner position.

County Coordinates
NAD 83 (1996 Adjustment)
N-196003.777
E-570434.636