

Statement of Evidence:

A021

The North Quarter Corner of Section 2, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.
- | | | |
|--------------|--------|--------------|
| 10" Tamarack | S 72 W | 16 links |
| 12" Tamarack | N 68 E | 25 links |
| 6" Tamarack | East | 17.46 chains |
| 30" Pine | West | 17.05 chains |
- 1901 County Road Book, pages 206 and 266, shows road surveyed by John Whilt, County Surveyor, running from this corner south on $\frac{1}{4}$ section line.
- 1919 Nels Peterson, Morrison County Surveyor, notes he set a concrete monument at all government corners along the south line of Lakin Township in Morrison County.
- 2006 Benton County Surveyor's Office found a rebar in a concrete monument in a swamp 1 foot under water. The monument is 2655.02 feet from the Northeast corner and 2648.19 feet from the Northwest corner of Section 2. This position fits the split between Section corners fairly well and the monument matches the monument set by Peterson in 1919. The monument was accepted as the Obliterated Quarter corner.

County Coordinates
NAD 83 (1996 Adjustment)
N-195954.846
E-565176.214