

Statement of Evidence:

A041

North Quarter Corner of Section 4, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

8" Blk Ash	S 56 W	11 links
8" Butternut	N 50 E	35 links

Line trees were noted as a 40" Pine East 16.60 chains and a 6" Pine West 19.65 chains.

1914 Morrison County Surveyor's Record Book A, on page 135 and page 158, shows a survey by Phil S. Randall of Section 33, 39-28 for laying out a town road running on north-south $\frac{1}{4}$ line. This corner is shown marked by a stake set 2640 feet east of SW corner and 2640 feet west of the SE corner.

1919 Nels Peterson, Morrison County Surveyor, notes he set a concrete monument at all government corners along the south line of Lakin Township in Morrison County.

1982 William Lunser, LS 9394, set a cast iron monument at a fence line north/south and a fence line east/west. He filed a Certificate of Location (#173441) and notes a distance of 2644.27 feet to the NW corner Sec 4 and a distance of 2649.54 feet to the NE corner Sec 4.

2003 Westwood Professional Services, Inc. found the CIM set by Lunser with the concrete monument set by Peterson lying flat on the ground along side and 2 feet east of the CIM. Accept the CIM as marking the position of where the concrete monument had been.

County Coordinates by side tie to CIM
NAD 83 (1996 Adjustment)
N- 196061.611
E- 554575.858