

Statement of Evidence:

A081

North Quarter Corner of Section 8, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

9" Maple	N 36 1/2 W	16 links
10" B. Oak	S 58 1/2 W	21 links

1913 County Surveyor's Record Book 2, page 306, contains a survey of a town road on the north line of Section 8 by M. J. Cleveland that shows corner found OK and notes distances of 2676 feet to the NW corner and 2687 feet to the NE corner.

1915 County Surveyor's Record Book 2, page 318, and County Surveyor's Record Book A, Map No. 4, shows a survey of Section 5 by J.P. Soderstrum. He notes an iron in the centerline of a road for the corner.

1939 County Engineer's Notebook No. 128 contains survey of CAR 22 running west to east on section line. No corner is shown, but stationing gives distances of 2660.1 feet to the NE corner and 2700.0 feet to the NW corner to a fence line north.

1963 County Engineer's Notebook No. 249 contains survey of CAR 22 running west to east on section line. No corner is shown, but stationing gives distances of 2677.3 feet to the NE corner and 2682.7 feet to the NW corner to a fence line south.

2001 Westwood Professional Services, Inc. set a 1/2" iron monument capped RLS #23002 at the centerline of County Road 22 (running east and west) and a fence line from the north. Corner is 2677.62 feet from the NW corner and 2684.41 feet from the NE corner.

On September 21, 2001 Westwood Professional Services, Inc. found the 1/2" iron monument capped RLS #23002 and removed the iron and placed a cast iron monument at the location and established reference ties.

2008 Westwood Professional Services, Inc. found a CIM 1.5 feet north of the centerline of County Road 22. Measured 2677.88 to the NW corner and 2684.28 to the NE corner of Section 8 with agrees with 1913 and 1963 county records. CIM is accepted as marking the obliterated position for this corner.

County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-190670.214
E-549574.104