

Statement of Evidence:

A091

The North Quarter Corner of Section 9, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

12" Birch	S 70 E	13 links
10" Sugar	N 6 W	30 links

1939 County Engineer's Notebook No. 128 contains survey of CAR 22 running west to east on section line. Corner is shown in center of road and with town road north-south. Stationing gives distances of 2593.4 feet to the NE corner and 2589.9 feet to the NW corner.

1963 County Engineer's Notebook No. 249 contains survey of CSAH 22 running west to east on section line. Corner is shown as a spike set in center of road in line with town road south. Ties:

Cor FP	NE	42.15
Cor FP	SE	41.2

Stationing gives distances of 2596.7 feet to the NE corner and 2586.5 feet to the NW corner with the point being a POT.

1982 William Lunser, LS 9394, set a cast iron monument at an occupation line north/south and a straight line between the NE and SE corners of Section 9. He filed a Certificate of Location (#173447). He notes a distance of 2586.50 feet to the NW corner Sec 9 and a distance of 2596.20 feet to the NE corner Sec 9.

2003 Westwood Professional Services, Inc. found a CIM and measured 2586.50 feet to the NW corner and 2596.22 feet to the NE corner of Section 9.
County Coordinates obtained by GPS to CIM:
NAD 83 (1996 Adjustment)
N- 190621.120
E- 554844.639