

**Statement of Evidence:**

North Quarter Corner of Section 10, Township 38 North, Range 28 West, Granite Ledge Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

- 1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Tamarack	N 4 E	8 links
9" Tamarack	S 15 W	19 links

- 1967 County Engineer's Notebook No. 267 contains survey of CSAH 22 running west to east on section line. Corner is shown as a spike set in center of road in line with fence south. Ties:

PP	S	40.25
Anc. P	SE	67.95

Stationing gives distances of 2661.3 feet to the NW corner and 2477.7 feet to the NE corner with deflection angle of 1-28' left.

- 1995 David Regan, LS 12236, notes an iron pipe set on fence line south and centerline of road.

- 1992 Paul Wollen, LS 10461, measured the north line of Section 10:

NW to N ¼ corner	= 2661.20 feet
N ¼ to NE corner	= 2477.78 feet

- 2001 On December 3, 2001 Westwood Professional Services, Inc. found a cast iron monument at the centerline of County Road 22 (running east and west) and noted reference ties as:

Found Nail & BC in PP	NE	77.10
Found PK in PP	SSE	42.39

- 2005 BWK found CIM and located using GPS.

County Coordinates

NAD 83 (1996 Adjustment)

N- 190606.854

E- 560102.363

Results in distances of 2661.71 feet to the NW corner and 2477.37 feet to the NE corner with a deflection angle of 1-17-49. CIM accepted as marking the obliterated position of the corner.