

Statement of Evidence:

A181

North Quarter Corner of Section 18, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Tamarack	N 28 E	13 links
14" Tamarack	S 49 1/2 E	29 links

1880 County Surveyor's Record Book 2, page 309, shows a road survey by Frank Sanders. Ran road survey from South ¼ corner of Section 18 north to ¼ post at North ¼ corner of Section 18 with a distance of 80.40 chains.

2008 Ben O'Malley performed a survey in Section 7 of Township 38 North, Range 28 West and set an iron pipe capped RLS 42300 at a 3-way fence corner to mark the corner position.

2010 The Benton County Surveyor's Office found the 1/2" iron pipe capped RLS 42300 from 2008 on an east-west fence and fence to the north. The position falls approximately 9 feet north of a straight line between section corners. The iron pipe measures 2623.03 feet to the northeast corner and 2326.76 to the northwest corner of Section 18 and fits a split of the distances at the east sixteenth to a fence south within a foot. The distance south measures approximately 40 feet long of the 1880 distance, though a measurement index to Mr. Sanders is unknown and the iron pipe falls on the extension of the north-south centerline. No additional information was found at the 1880 resurvey distance. Since the found iron pipe fits line between section corners within 9 feet, the long-standing fences east-west and north, the GLO distance to the east within 17 feet, a split of the fences at the east sixteenth and the extension of the fence to the south, it is accepted as marking the obliterated corner position.

County Coordinates
NAD 83 (1996 Adjustment)
N-185495.306
E-544461.912