

Statement of Evidence:

A191

North Quarter Corner of Section 19, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Bur Oak	S 65 W	20 links
12" Sugar	N 33 W	41 links

1880 County Surveyor's Record Book 2, page 306, contains a survey by Frank Sanders for a town road run north to the North ¼ corner of Section 18 and south 16.84 chains on ¼ line to state road.

1937 County Engineer's notebook No. 143 contains a road survey by H. G. Elletson for SAR No. 12. Notes show road survey run west to east on section line, but road never built. Corner is shown as a spike in center of north-south road with fence line west with ties:

F. P.	NW	24.4'
F. P.	SW	29.7'
F. P.	SE	16.2'
14" Elm Stp	NE	41.75'

Stationing gives distances of 2265.9 feet to the NW corner and 2700.0 feet to the NE corner of Section 19.

1948 County Engineer's Notebook 167 contains road survey along north line of Section 19 (same stationing as 1937 notes). Road never built. Corner is shown marked by a hub with same ties. Delta angle of 0-49' left is given (running west to east).

2004 Westwood Professional Services, Inc. found a ¾ " iron pipe in north-south road and in line with field line west. Distance south to Daisy Road checked with 1880 survey. Measured 2266.84 feet to the NW corner and 2700.58 feet to the NE corner, which checked with 1937 survey. Measured delta angle is 0-43-48 left, which checked with 1948 survey. Accepted found pipe as marking the obliterated corner position.
County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N- 180146.672
E- 544468.878

2010 The Benton County Surveyor's Office found the 3/4" iron pipe. The 2004 coordinates were verified and reference ties were taken.