

Statement of Evidence:

A201

North Quarter Corner of Section 20, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

12" Blk Oak	S 74 1/2 E	43 links
14" W Pine	N 59 W	12 links

Line trees are noted as: 36" W Pine East 37.02 chains and 18" Blk Oak West 30.44 chains.

1937 County Engineer's notebook No. 143 contains a road survey by H. G. Elletson for SAR No. 12. Notes show road survey run from west to east, but road never built. Survey does not call for corner, but by stationing shows north-south fence 2678.1 feet east of the NW corner and 2620.2 feet west of the NE corner of Section 20.

1948 County Engineer's Notebook 167 contains road survey for SAR No. 12. Notes do not show corner, but stationing shows fence south at 2637.1 feet from NW corner and 2660.5 feet from NE corner.

2001 Westwood Professional Services, Inc. established this corner as lost at the split and on line and on September 21, 2001 set a 3/4" Aluminum Monument capped "Benton County Monument" at the corner location. This corner is 2649.31 feet from the NE and NW Cor Sec 20 and is 13 feet east of fence line south. We established reference ties.

2004 Westwood Professional Services, Inc. located monument:
County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N- 180086.527
E- 549816.064

Note: Distance between section corners checks with 1937 and 1948 surveys.
Based on 1937 survey, corner based on fence line could be 29 feet west. Based on 1948 survey, corner based on fence line could be 12 feet west.