

**Statement of Evidence:**

**A211**

North Quarter Corner of Section 21, Township 38 North, Range 28 West, Granite Ledge Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post and bearing trees were recorded.

12" Birch	S 52 E	14 links
12" Birch	N 55 W	41 links

1948 County Engineer's Notebook 167 contains road survey for SAR No. 12. Notes do not show corner with distance for the north line being 5127.6 feet.

1997 Dave Regan, LS 12236, found a MN/DOT R/W Monument, south of the back slope of an east/west road, 30 feet +/- north of a fence line.

2001 Westwood Professional Services, Inc. found a MN/DOT R/W Monument, aluminum cap fastened to steel fence posts, 15 feet south of the centerline of east-west road. We recorded ties to existing tie points set by MN/DOT.

Nail & Disc in 14" Ash	SSW	24.50
Nail & Disc in 14" Twin Ash	SE	24.45
Nail & Disc in 12" W. Oak	NW	64.25

2002 The St. Cloud and Brainerd offices of MN/DOT were contacted for information. They could only find a coordinate file for the project, but could not find any other information, although Jim Kramer and Sam Deleo remember that it had been done. They did not have coordinates on this corner, only the section corners east and west. Believe MN/DOT may have set the corner lost, but will have to wait until the line can be measured. Using MN/DOT coordinates the distance between section corners is 5127.11 feet.

2003 No resurvey information was found on this corner in the Benton County Surveyor's records.

2005 Certificate of Survey by Daniel Kron, LS 42621, gives a distance of 2563.46 feet to the NE corner.