

Statement of Evidence:

A291

North Quarter Corner of Section 29, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

9" Elm	S 19 E	8 links
7" Ash	N 57 E	5 links

1880 County Surveyor's Record Book 2, page 306, contains a survey by Frank Sanders for a town road run west from this corner with a distance of 39.86 chains to the NW corner of Section 29.

1913 County Surveyor's Record Book 2, page 306, contains a survey for a town road between Sections 20 and 29 by M.J. Cleveland. At 2661 feet from the NW corner he found both stumps of GLO BT's ok and set a stone on end for the corner. He measured 5316 for the mile.

2004 Westwood Professional Services, Inc. found a ½" iron pipe with cap No. 9394 (Lunser) in a pasture at the lost position. Measured 2654.49 feet to the NW corner and 2654.62 feet to the NE corner. This fits within 7 feet of Cleveland's distance for the mile, which means the iron should be within 3 feet east-west of the stone set by Cleveland. A quick search of the area did not identify a stone as the one set by Cleveland. The pasture is full of field stones and a more thorough search is needed.

County Coordinates obtained by GPS to iron pipe (9394):
NAD 83 (1996 Adjustment)
N- 174808.614
E- 549866.346