

Statement of Evidence

A072

The Northeast Corner of Section 7, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post and bearing trees were recorded.
30" Pine N 39 1/2 W 39 links
14" Aspen S 38 E 10 links

1913 County Surveyor's Record Book 2, page 306 contains a road survey between Sections 5 and 8 by M.J. Cleveland dated July 17, 1913. Notes state that he found stump of Pine and set a post for the corner with new tie:
NW corner School S 40 E 116 feet.

1915 County Surveyor's Record Book 2, page 318, and County Surveyor's Record Book A, Map No. 4 shows a survey of Section 5 by J.P. Soderstrum. He found a stake at the centerline of roads from the west, east and south.

1933 County Engineer's notebook No. 68 for SAR 6 shows hub at corner with ties:
F.P. SW 49.6'
F.P. NW 62.3'
Notes show town road east and west.

1939 H. G. Elletson (County Engineers' Notebook No. 128) notes a hub at this location with the following reference ties.
SW Cor. Store foundation NE 64.5
F.P. NW 62.3

1953 County Engineer's Notebook No. 196 contains a road survey for SAR 6 running from south to north on section line. Corner is shown marked as an iron in center of road with CAR 22 east and west. Same ties as 1953 below.

1953 County Surveyor's Record Book 2, page 322, notes that an iron marked this corner with the following reference ties.
SW Cor. Store NE 72.9
P.P. NW 61.85
P.P. SW 54.5
NW Cor. School SE 161.3
Highway stationing shows corner at PI 397+64.9 with a deflection 0-36 left. (same delta as 1933).

1963 County Engineer's Notebook No. 249 contains survey of CSAH 22 running west to east on section line. Corner is shown as a spike set in center of road intersection with CSAH 6 north-south. Ties:
PP SW 54.5
PP NW 61.85

1983 On July 28, 1983 William Lunser, LS 9394, found a 3/4" iron pin at the intersection of the centerlines of two County Roads North-South and East-West. He placed a cast iron monument at said location and established reference ties and filed a Certificate of Location (#173443). Shows tie of 65.28 feet NE to southwest corner of store.

2001 On September 21, 2001 Westwood Professional Services, Inc. found a RR spike at the intersection of the centerlines of County Road 22 (running east and west) and County Road 6 (running north and south). Removed RR spike and placed a cast iron monument at the location and established reference ties. Tie to store 65.51 feet.

NOTE: CORNER NEEDS FURTHER CHECKING.

County Coordinates
NAD 83 (1996 Adjustment)
N-
E-