

Benton County Surveyor's Office
Jerome C. Wittstock, County Surveyor
Minnesota License No. 19552

Statement of Evidence

A082

The Northeast Corner of Section 8, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

28" W. Pine	N 40 W	10 links
12" Lind	S 49 E	8 links

1913 County Surveyor's Record Book 2, page 306, contains a survey of a town road on the north line of Section 8 by M. J. Cleveland and shows he found GLO bearing tree to the north OK for the corner and notes a new B.T.

8" Red Elm	N 90 W	67'
------------	--------	-----

1915 County Surveyor's Record Book 2, page 318, and Record Book A, Map No. 4, show a survey of Section 5 by J.P. Soderstrum. He notes a stake at the corner as established by Cleveland.

1930 County Engineer's notebook No. 56 contains a road survey by H. G. Elletson for CAR No. 27. Notes show road survey run south to north along section line. Corner marked by an iron monument with ties:

4" W. Oak	NE	44.9'
F.P.	NW	46.5'

1939 County Engineer's Notebook No. 128 contains survey of CAR 22 running west to east on section line. Corner is shown as an iron in center of 4-way road intersection.

1963 County Engineer's Notebook No. 249 contains survey of CSAH 22 running west to east on section line. Corner is shown as an iron in center of road intersection with CH 67 running north-south. Ties:

TP	SE	51.2
----	----	------

Other ties are the same as in 1967 listed below.

1967 County Surveyor's Record Book 2, page 324, notes an iron monument at the corner with the following reference ties.

P.P.	NE	55.7
Cor F.P.	NW	62.25
T.P.	SW	53.0

1982 William Lunser, LS 9394, found an axle shaft at the intersection of the centerline of roads running North, South, East and West. He set a cast iron monument and established reference ties and filed a Certificate of Location (#173446).

2001 Westwood Professional Services, Inc. found a cast iron monument at the intersection of the centerlines of County Road 22 (running east and west) and Township Road 67 (running north and south). We left monument as found and established reference ties.

2003 Westwood Professional Services, Inc. found CIM and obtained coordinates by GPS. No evidence found of 1913 tie tree. Lunser's tie to PP NE fits with 1967 ties.
County Coordinates to CIM
NAD 83 (1996 Adjustment)
N- 190650.195
E- 552258.305

2010 Benton County Surveyor's found a cast iron monument at the intersection of CSAH 22 and CSAH 67. This position agrees with all records previous. The coordinates match the coordinates from Westwood in 2003. The CIM is accepted as the Obliterated Section corner.