

Statement of Evidence:

A102

Northeast Corner of Section 10, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

16" Sugar	N 85 1/2 W	30 links
12" Birch	N 42 1/2 E	34 links

1967 County Engineer's Notebook No. 267 contains survey of CSAH 22 running west to east on section line. Corner is shown as iron in center of road in line with fence lines north and south. Ties:

PP	North	33.6
12" W. Oak	NE	77.95
4" R. Oak	South	44.9

1973 William Lunser, LS 9394, set a RR spike for the corner at the intersection of the center of east-west road and fence lines north-south. Filed Certificate of Location (Doc. No. 137344) which shows 12" Oak NE 77.08.

2005 BWK located RR spike by GPS.
County Coordinates
NAD 83 (1996 Adjustment)
N- 190677.034
E- 562578.742

2008 Westwood Professional Services, Inc. found a railroad spike ~3 feet north of the centerline of County Road 22 and on line with fences north and south. Field crew noted finding an oak stump fitting 1967 tie and two stumps from Lunser's 1973 certificate. Railroad spike is accepted as marking the obliterated position for this corner. Coordinates obtained by GPS coincide with 2005 BWK position.