

**Statement of Evidence:**

**A112**

Northeast Corner of Section 11, Township 38 North, Range 28 West, Granite Ledge Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" W Birch	S 87 W	12 links
10" Sugar	N 21 1/2 E	37 links

1901 County Road Book, pages 206 and 266, shows road surveyed by John Whilt, County Surveyor, running west and south from this corner.

1937 County Engineer's Notebook No. 82 contains a road survey for SAR No. 9 running south to north and terminating at this corner. Notes show corner marked by an iron with road east-west. Ties:  
Cor. FP SE 38.8'  
Cor. FP NE 22.15'

1957 County Surveyor's Record Book 2, page 330, contains ties to an iron that are the same as listed above in 1937 and below in 1967.

1962 County Engineer's Notebook No. 269 contains a road survey for CSAH No. 9 running south to north. Notes show corner marked by an iron in center of road intersection. Same ties as listed below in 1967.

1967 County Engineer's Notebook No. 267 contains survey of CSAH 22 running west to east on section line. Corner is shown as an iron in center of 4-way road intersection. Ties:  
T.P. NW 42.3'  
PP SE 49.2'  
SW Cor. House Found. NE 110.8'

1973 William Lunser, LS 9394, found an iron monument in road intersection. Left monument as found and filed a Certificate of Location (Doc. No. 137342). Tie to SW corner of house foundation is NE 110.92'. Distances shown on Certificate: 2646.73 feet to the North 1/4 corner of Section 11 and 2649.70 feet to the East 1/4 corner of Section 11.

2004 Dan Kron, LS 42621, reported using corner for survey in Section 1. Ties:  
PP (PK Nail) SE 65.6'  
Cor. FP (PK Nail) NW 64.16'  
Tel Ped. (PK Nail) NE 43.07'

2005 WSN found rebar in road intersection.  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N- 190768.118  
E- 567868.555

2008 Westwood Professional Services, Inc. found a 1/2" rebar in road intersection north/south/east/west. We found one 1973 tie remaining and measured 2647.00 feet to the N1/4 and 2649.55 feet to the E1/4 of Section 11 which agrees with Lunser information. Rebar is accepted as marking the obliterated position for this corner. Coordinates obtained by GPS coincide with 2005 WSN position.