

Statement of Evidence:

A122

Northeast Corner of Section 12, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

8" Sugar	S 61 W	41 links
12" Basswood	N 51 1/2 W	54 links
8" Sugar	N 73 E	8 links
10" Elm	S 78 E	9 links

No Date (Old) County Surveyor's Record Book 2, page 332, lists new BT:
W. Oak stump N 39 E 50 links

1983 & 1996 Corner was established by John Oliver, LS 8194, Mille Lacs County Surveyor. His statement of evidence refers to Mille Lacs County Surveyor records in 1912 and 1918 from which he based the corner position. For details see his Certificate of Location filed as Doc. No. 244635.

County Coordinates from John Oliver & Associates by traverse
NAD 83 (1996 Adjustment)
N- 190769.036
E- 573171.943

2004 Dan Kron, LS 42621, used corner for survey in Section 1.

2005 WSN found 1" iron pipe with broken cap.
County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N- 190769.422
E- 573171.553

2008 Westwood Professional Services, Inc. found a 1" iron pipe fitting 1996 Oliver ties. After analysis of the statement of evidence from Oliver's certificate, I agree with his method of perpetuating this corner. 1" iron pipe is accepted as marking the obliterated position for this corner.
County Coordinates Obtained by GPS coincide with 2005 WSN position.