

**Statement of Evidence:**

**A132**

The Northeast Corner of Section 13, Township 38 North, Range 28 West, Granite Ledge Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

12" Sugar	S 68 E	21 links
10" Sugar	N 23 E	45 links
8" Sugar	N 68 W	58 links
8" Sugar	S 45 W	39 links

No Date County Surveyor's Record Book 2, page 334, (Old) lists new BT's:

10" W. Pine	S 25 ½ W	138 links
7" W. Pine	S 42 ½ E	273 links

1996 John Oliver, LS 8194, Mille Lacs County Surveyor set corner at single proportion distance based on Judicial Road survey. He set a CIM and filed Certificate of Location (Doc. No. 244637). See his statement of evidence for details  
County Coordinates from John Oliver & Associates by traverse:  
NAD 83 (1986 Adjustment)  
N- 185480.368  
E- 573307.800

2001 Dennis Pederson, LS 16095, used CIM for survey in Section 13.

2008 Westwood Professional Services, Inc. found a CIM fitting 1996 Oliver ties. After analysis of the statement of evidence from Oliver's certificate, I agree with his method of perpetuating this corner. CIM is accepted as marking the obliterated position for this corner.  
County Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N- 185480.986  
E- 573307.336