

Statement of Evidence:

A142

Northeast Corner of Section 14, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office surveyor, Oscar F. Davis, set a wood post at this location and bearing trees were recorded.

10" Birch	S 60 E	33 links
20" B. Oak	N 55 W	52 links

1901 County Road Book, pages 206 and 266, shows road surveyed by John Whilt, County Surveyor, running north and south from this corner.

1937 County Engineer's Notebook No. 82 contains a road survey for SAR No. 9 running south to north. Notes show corner marked by a hub with town road east and fence west. Ties:

TP	NW	38.8'
FP	SW	37.65'

1962 County Engineer's Notebook No. 269 contains a road survey for CSAH No. 9 running south to north. Notes show corner marked by a spike set in center of road with town road east and fence line west. Ties:

P.P.	SE	54.1
F.P.	W	35.8
P.P.	NW	41.3

1995 David Regan, LS 12236, notes he set an iron pipe in the centerline of roads north/south and east and fence line west.

2000 Dennis Pederson, LS 16095, Bogart, Pederson & Associates, Ins. found a 1/2 " iron pipe that fit with approximate County Highway position.

2001 Westwood Professional Services, Inc. found a 1/2" open iron pipe flush at the intersection of the centerlines County Road 9 (running north and south) and 155th Street NE (running from the east). We removed the iron and set a cast iron monument at the location and established reference ties.

2004 Found CIM and obtained coordinates by GPS.
County Coordinates
NAD 83 (1996 Adjustment)
N- 185421.491
E- 567972.371

2011 The Benton County Surveyor's Office found the cast iron monument 0.5 feet below the road surface and verified the 2004 coordinates. The cast iron monument is in the north-south centerline of CSAH No. 9, on centerline of 155th Street NE to the east and on the fence west as described in 1937, 1962 and 1995. The distance for the half mile north fits within one foot and south within 5 feet of the 1937 distances. The cast iron monument is accepted as marking the corner position.