

Statement of Evidence:

A152

Northeast Corner of Section 15, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

26" Birch	N 41 E	18 links
20" Tamarack	S 49 1/2 E	54 links

1949 County Surveyor's Record Book 2, page 338, shows measurement of 5282.0 feet along the north line of Section 15. (Note: this could be from an earlier date.)

1983 David Regan, LS 12236, set a 1/2 " iron pipe on fence lines east and south. He filed a Certificate of Location (Doc. No. 167995). (Note: Certificate shows fence lines west and south).

2004 Found iron pipe with cap No. 12236 and obtained coordinates by GPS. Measured 5266.26 feet to the NW corner.
County Coordinates
NAD 83 (1996 Adjustment)
N- 185460.575
E- 526840.763

2008 Westwood Professional Services, Inc, found an iron pipe capped 12236 at the intersection of downed fence lines running west and south. Measured 5266.26 feet along the north line of Section 15 which short of GLO by 5.16 feet and short of 1949 record distance by 15.74 feet. Searched area for any evidence of original bearing trees and nothing was found. Fence lines appear to be very old and the only possible physical evidence found in the area. 1/2" iron pipe capped 12236 is accepted as marking the obliterated position for this corner. County coordinates obtained by GPS coincide with 2004 position.