

Statement of Evidence:

A192

Northeast Corner of Section 19, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

14" LindS	51 E	12 links
18" Sugar	N 46 W	51 links

1933 County Engineer's notebook No. 68 for SAR 6 shows rock at corner with ties:

8" Oak	SE	85.3'
3" Elm	SW	48.8'

Notes show SAR 12 running east and SW.

1937 County Engineer's notebook No. 143 contains a road survey by H. G. Elletson for SAR No. 12. Notes show road survey run from west to east, but road never built. Corner ties:

8" Oak	SE	85.3'
3" Elm	SW	48.8'

1948 County Engineer's Notebook 167 contains road survey for SAR No. 12. Corner marked by a stone with same 1937 ties. Same stationing as 1937 with a delta angle of 3-20' left (running west to east).

1953 County Engineer's Notebook No. 196 contains a road survey for SAR 6 running from south to north on section line. Corner is shown marked by stone in center of SAR 12. Same ties as 1954 below.

1954 County Surveyor's Record Book 2, page 346 note that a rock is at the corner with the following reference ties.

8" W. Oak	SE	85.3'
3" Elm	SW	48.8'
2 nd F.P.	NE	57.05'

Highway plans show stone section corner at PI 291+10.8 with a delta of 0-25' Lt running south to north.

2001 Westwood Professional Services, Inc. found a RR spike at the corner location. Removed the RR spike and set a cast iron monument and established reference ties.

2004 Westwood Professional Services, Inc. found CIM. (Do not use!)

County Coordinates obtained by GPS

NAD 83 (1996 Adjustment)

N- 180037.367

E- 547167.245

2009 Benton County Surveyor's Office excavated a 10-foot by 10-foot by 3-foot deep hole to original ground. An 12-inch by 8-inch by 8-inch granite stone was found 3 feet below the road grade at natural ground level, in the north-south centerline of CSAH No. 6 and 4 feet south of the Daisy Lane east and west. The stone fits the 1933 distance south within 4 feet and north within 9 feet. The stone is accepted as marking the obliterated corner position. GPS coordinates were obtained and reference ties established.

County Coordinates obtained by GPS

NAD 83 (1996 Adjustment)

N- 180032.980

E- 547167.282