

Statement of Evidence:

A252

The Northeast Corner of Section 25, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office surveyor, Theodore Conkey, set a wood post at this location and bearing trees were recorded.

12" W. Oak	S 74 E	44 links
8" Elm	N 76 E	45 links
10" Basswood	N 29 W	37 links
12" Blk Ash	S 47 W	44 links

1902 County Surveyor's Record Book 2, page 358 and Record Book A, Map No. 37 show a survey of the subdivision of Section 25 by John Whilt. The type of monument at the corner is not given.

1921 Mille Lacs County: R. S. Chapman did a survey of Section 30, Township 38, Range 27 of Mille Lacs County. He notes a cut granite rock at this corner.

1961 County Surveyor's Record Book 2, page 358, shows a granite monument at the corner with ties:

T.P.	SW	67.7
P.P.	SE	52.6
5" W. Oak	NE	72.7

1994 John Oliver, LS 8194, Mille Lacs County Surveyor, dug with a backhoe and found said cut granite rock.

1996 John Oliver set a 1" X 14" iron pipe over the granite monument and filed a Certificate of Location (#244642).
County Coordinates from John Oliver & Associates by traverse
NAD 83 (1986 Adjustment)
N- 174900.321
E- 573566.284

2008 Westwood Professional Services, Inc. found 1" iron pipe cap #8194 at the intersection of roads north/south/west and fitting 1996 Oliver ties. Iron pipe is accepted as marking the obliterated position for this corner.
County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 174900.848
E- 573565.449