

**Statement of Evidence:**

**A262**

The Northeast Corner of Section 26, Township 38 North, Range 28 West, Granite Ledge Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office surveyor, Oscar F. Davis, set a wood post at this location and bearing trees were recorded.  
16" W. Birch N 35 E 21 links  
12" Lind S 65 W 22 links  
A line tree is noted: 30" W. Pine North 6.65 chains

1902 County Surveyor's Record Book 2, page 358 and Record Book A, Map No. 37 contains survey of Section 25 by John Whilt.

No Date County Surveyor's Record Book 2, page 354, notes the following additional bearing tree:  
6" W. Elm N 69 W 24 links

1937 County Engineer's Notebook No. 82 contains a road survey for SAR No. 9 running south to north. Notes show corner marked by a hub and brick with town road east and fence west. Ties:  
FP SE 43.3'  
FP NE 58.4'

1962 County Engineer's Notebook No. 269 contains a road survey for CSAH No. 9 running south to north. Notes show corner marked by an iron in center of road with town road east and fence line west. Same ties as listed below for 1969 and 1972.

1969 County Surveyor's Record Book 2, page 360, notes an iron at the corner in 1969 and 1972.

F.P. W 64.05  
F.P. NE 78.7  
P.P. NE 57.1

Undated ties.

T.P. SW 47.85  
F.P. W 58.4  
F.P. NE 72.3

2001 David Regan, LS 12236, notes a found T-bar in the centerline of roads north-south and east.

2001 On November 21, 2001 Westwood Professional Services, Inc. found an iron monument capped RLS #12236 next to a T-post at the intersection of the centerlines of County Road 9 (running north and south) and 135<sup>th</sup> Street NE. Removed the iron monument and placed a cast iron monument over the T-post and established reference ties. No evidence of previous ties or bearing trees was found.

2003 Westwood Professional Services, Inc.  
County Coordinates by GPS to CIM:  
NAD 83 (1996 Adjustment)  
N- 174880.261  
E- 568159.279