

Statement of Evidence:

A292

Northeast Corner of Section 29, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

40" Pine	S 15 1/2 E	63 links
30" B. Oak	N 3 E	25 links

1913 County Surveyor's Record Book 2, page 306 contains a survey for a town road between Sections 20 and 29 by M. J. Cleveland, District Engineer. He found stump of GLO Pine BT's and wood stake ok and set a 1 1/2 " x 2 feet gas pipe with 3 small stones at the sides for the corner. He measured 5316 for the mile.

1915 County Surveyor's Record Book 2, page 362, shows Soderstrum found pipe set by Cleveland.

1930 County Engineer's notebook No. 56 contains a road survey by H. G. Elletson for CAR No. 27. Notes show road survey run south to north along section line. Corner marked by an iron pipe with ties:

4" Poplar	E	57.5'
6" Oak	SE	78.6'

1962 County Surveyor's Record Book 2, page 366 notes an iron at the corner with the following reference ties.

4" Poplar	E	73.8
6" Basswood	SE	89.2

Older ties:

4" Poplar	E	57.5
6" Oak	SE	78.6

2001 Westwood Professional Services, Inc. found a 1/2" iron pipe at the centerline of Township Road 67 (previously found in 2000). Also found a Basswood clump that fit with the 1962 distance to a 6" Basswood. Removed the iron monument and set a cast iron monument and established reference ties.

2002 Certificate of Location filed as Doc. No. 291178.

2004 County Coordinates obtained by GPS to CIM:
NAD 83 (1996 Adjustment)
N- 174853.211
E- 552520.589

CORNER SHOULD TO BE EXCAVATED TO VERIFY!