

**Statement of Evidence:**

**A312**

Northeast Corner of Section 31, Township 38 North, Range 28 West, Granite Ledge Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

14" B. Ash	? 53 W	33 links
10" Blk. Ash	S 30 E	37 links

1933 County Engineer's notebook 68 shows hub set at corner on fence lines west and east with ties:

T. P.	E	24.0'
F.P.	NE	28.0'

Highway station 52+48.5 with a delta of 2-16' left (running south to north).

1954 County Surveyor's Record Book 2, page 370 notes a hub set marking this corner with the following reference ties:

5" Elm	E	61.7
P.P.	SW	44.5

County Highway plans and notes in Notebook No. 196 show corner at PI 187+57.1 with a delta 2-22' Lt. Ties from 1933 are also shown.

1988 County Highway plans show corner assumed at PI 597+14.32

2000 David Regan, LS 12236, notes he found a RR spike in the centerline of a north-south road and a fence line east.

2001 Westwood Professional Services, Inc. found a RR spike at the intersection of the centerlines of County Road 6 (running north and south) and field approaches (running east and west). Tie to PP SW checks with Book 2, page 370 record. Removed monument and placed a cast iron monument at the location of the corner and established reference ties.

2004 County Coordinates obtained by GPS to CIM:

NAD 83 (1996 Adjustment)  
N- 169684.681  
E- 547321.660