

Statement of Evidence

A332

Northeast Corner of Section 33, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

16" Elm	S 49 E	100 links
10" W. Birch	N 79 1/2 E	77 links

1901 County Road Book, pages 206 and 266, shows road surveyed by John Whilt, County Surveyor, running north and south from this corner.

1915 County Surveyor's Record Book 2, pages 362 and 363 and Record Book A, Map No. 13 shows a survey by J.P. Soderstrum of Section 27. He found the old stake, which was set by Whilt in 1897. He found no original BT's.

1924 County Highway plans for SAR No. 7 show corner in road intersection with ties.

1963 County Surveyor's Record Book 2, page 374, shows an iron at the corner with the following reference ties.

P.P.	SE	68.9
24" Elm	NE	93.0
T.P.	NW	50.85

County Engineer's Notebook No. 231 contains a road survey for CSAH 7 running north from this corner. Notes show spike set in center of road intersection with town road east and west. Same ties.

1924 ties:

Cor FP	SW	46.5
Cor FP	NW	44.6

2001 Westwood Professional Services, Inc. found a 1/2" solid pin at the intersection of the centerlines of County Road 7 (running north and south) and 125th Street NE (running east and west). Iron was 0.84 feet north of a PK nail at the surface. Iron fit 1963 tie to PP. Other 1963 ties are gone. Removed and set a cast iron monument and established reference ties.

2004 County Coordinates obtained by GPS (CIM):
NAD 83 (1996 Adjustment)
N- 169683.629
E- 557741.627