

Statement of Evidence:

A352

Northeast Corner of Section 35, Township 38 North, Range 28 West, Granite Ledge Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

24" Sugar	S 89 E	80 links
10" Birch	N 62 W	34 links

1902 County Surveyor's Record Book A, Map No. 37, shows a survey of Section 25 by John Whilt. Corner is shown, but no information.

No Date County Surveyor's Record Book 2, page 358, notes the following additional bearing tree.

10" W. Pine	S 85 3/4 E	127 links
-------------	------------	-----------

1937 County Engineer's Notebook No. 82 contains a road survey for SAR No. 9 running south to north. Notes show corner marked by a spike in road intersection with ties:

FP	NW	49.3'
FP	SW	39.9'

1962 County Engineer's Notebook No. 269 contains a road survey for CSAH No. 9 running south to north. Notes show corner marked by an iron in center of road with town road east and west. Ties:

PP	SW	55.8'
2 nd FP	SE	61.5'
TP	NE	41.7'

1962 County Surveyor's Record Book 2, page 378, notes an iron at the corner with the same ties as above in 1962. (Notation shows same in 1969 and 1972)

2000 Westwood Professional Services, Inc. set an iron pipe capped RLS #23002 at the intersection of the centerlines of County Road 9 (running north and south) and 125th Street NE (running east and west).

2001 Westwood Professional Services, Inc. found an iron pipe with a busted cap at the intersection of the centerlines of County Road 9 (running north and south) and 125th Street NE (running east and west). We removed the iron and set a cast iron monument at the location and established reference ties. Tie to PP to the SW checked within a foot, but could be a different pole. No evidence found of the W. Pine BT.

County Coordinates by GPS to CIM

NAD 83 (1996 Adjustment)

N- 169632.977

E- 568205.201