

Statement of Evidence:

K132

Northeast Corner of Section 13, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Corner established by GLO and marked by a wood post with bearing trees noted as.

12" Blk Ash	N 60 W	40 links
12" Elm	N 39 E	72 links
10" Elm	S 37 W	28 links
10" Basswood	S 44 E	18 links

Line trees were noted as a 18" Blk Oak South 24.59 chains and a 16" Blk Ash North 15.28 chains.

1933 County Engineer's notebook No. 67 shows road survey by H. G. Elletson starting at this corner and running west. Corner is shown as a spike in center of road with fence north with ties:

36" Willow	NE	55.4'
30" Willow	SE	46.3'

2005 WSN searched corner area and did not find any corner marker and no evidence remains of the 1933 ties. Set a PK nail for a temporary corner in the center of east-west road and in line with old fence line north. Distance to the North $\frac{1}{4}$ corner of Section 13 checks reasonably with the 1933 highway survey.

County Coordinates obtained by GPS to PK nail:

NAD 83 (1996 Adjustment)

N- 122039.158

E- 542664.334

Accepted PK Nail position as the best evidence of the obliterated corner position and replaced the PK Nail with a $\frac{1}{2}$ " iron pipe.