

**Statement of Evidence:**

**K211**

The North Quarter Corner of Section 21, Township 36 North, Range 29 West, St. George Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post was set and bearing trees were recorded

7" Bur Oak	N 29 W	33 links
10" Bur Oak	N 34 1/2 E	63 links

1999 William Lunser, LS 9394, set a 1/2" iron pipe in the centerline of roads east/west and near a field line south using lost methods east-west and center of road for north-south position. He filed a Certificate of Location (#283124) and notes a distance of 2606.06 feet to the NE and NW corners Sec 21. He had found a 1/2" square iron pin 2610.70 feet west of the NE corner and 2596.05 feet east of the NW corner or 7.3 feet west of the lost position, which he did not use as the corner.

2002 No resurvey information was found on this corner in the Benton County records. Question why the found square pin was not used in 1999.

2008 The County Surveyor's Office searched and found a 1/2" capped iron pipe 0.3 ft. under the centerline of the east-west gravel road (25<sup>th</sup> Street N.E.) and on line with a wire fence to the south. Distances to the NW and NE corners give 2603.82 ft. and 2603.11 ft., respectively, which agrees with Lunser's 1999 position. The Surveyor's Office also found a 1/2" square pin, of unknown origin, approximately 7.7 feet west of said 1/2" capped iron pipe. The Surveyor agrees with Lunser's position as marking the obliterated corner and updated ties to same.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-116501.374

E-524291.989