

Statement of Evidence:

K191

The North Quarter Corner of Section 19, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established this corner set a wood post at this location and bearing trees were recorded.

6" B. Oak	S 39 E	108 links
6" B. Oak	S 50 E	112 links

2001 Westwood Professional Services, Inc. found a 1/2" iron pipe near a fence corner. The fence lines come from the east and the south and we accepted the pipe as marking the obliterated corner position. We removed the 1/2" iron pipe and placed a cast iron monument at its location.

We measured 5693.09 feet between section corners. The GLO distance is 79.72 chains (5261.52 feet). It is apparent along the west closing sections of this township that the original GLO surveyor did not run the last 1/2 mile of the east-west section lines. The last 1/2 miles are 300 to 500 feet longer than reported in the GLO notes. We measured 2734.64 feet to the NE Cor Sec 19. The found pipe is 8.8 feet north of a straight line and 121.90 feet east of lost position. Using the pipe found in the center of Section 18 fits a fence line south.

County Coordinates Obtained by GPS (1/2" Iron Pipe):

NAD 83 (1996 Adjustment)
N-116255.016
E-513712.849

2003 Certificate of Location filed as Document No. 295390.