

**Statement of Evidence:**

**K033**

East Quarter Corner of Section 3, Township 36 North, Range 29 West, St. George Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked by a wood post with bearing trees:

24" W Oak                      S 1 ½ E                      832 links

1929 County Surveyor's Record Book 1, page 89 and County Surveyor's Record Book A, Map No. 50 is a survey of Section 3 by H. G. Elletson showing a complete section subdivision with all 1/16<sup>th</sup> corners set. Elletson notes an iron monument at the corner and a distance of 2581.3 feet to the NE Corner Sec 3 and 2589.4 feet to the SE Corner Sec. 3. The corner is referenced at the intersection of 4 fences. (Notes in Notebook 48)

1986 William Lunser, LS 9394, searched for and found nothing. He set a cast iron monument at the intersection of fence lines north/south/east. He filed a Certificate of Location (#191240).

2001 Sam Deleo, LS 40341, found a the cast iron monument set in 1986 and also found a 1 ½" iron rod with a rounded head and a wood stake 7.5 feet south of the cast iron monument. The iron rod fit the 1929 survey. He removed the cast iron monument and replaced it with a ½" iron pipe and lowered the 1 ½" iron rod and set the cast iron monument over it. He filed a Certificate of Location (279108). Distances measured from the rounded 1 ½" iron rod to the NE corner Sec 3 is 2583.72 feet and to a found iron rod at the SE corner of the NE ¼ of the NE ¼ is 1321.59 feet, which both fit reasonably well with the 1929 survey.

2004 From CIM measured 2583.75 feet to the NE corner and 2588.16 feet to the SE corner. These distances confirm that the CIM now marks the 1929 position.  
County Coordinates Obtained by GPS to CIM.  
NAD 83 (1996 Adjustment)  
N- 129755.706  
E- 531937.152