

Statement of Evidence:

K315

South Quarter Corner of Section 31, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post with bearing trees noted as:

12" Tamarac S 72 1/2 E 29 links

12" Tamarac N 87 1/2 W 36 links

A line tree was noted as a 6" Tamarac East 21.04 chains

Pre 1940 MN/DOT notes by C. H. West for TH 95 show scribed stake 0.6 feet south of centerline. Stationing gives distances of 2623.6 feet to the SW corner and 2644.4 feet to the SE corner.

2000 Sherburne County Surveyor's Office found 1 1/4 " iron pipe per Document No. 177861 and prepared new Certificate of Location.

County Coordinates converted from Sherburne County Coordinates:

NAD 83 (1986 Adjustment)

N- 100064.29

E- 513656.77

Using coordinates converted from Sherburne County gives distances of 2609.90 feet to the SW corner and 2654.33 feet to the SE corner.

NOTE: APPEARS C. H. WEST FOUND CORNER APPROXIMATELY 12 FEET EAST. APPEARS 1 1/4" IRON PIPE WAS SET LOST.

County Coordinates

NAD 83 (1996 Adjustment)

N-

E-