

Statement of Evidence:

L143

East Quarter Corner of Section 14, Township 36 North, Range 30 West, Minden Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey established this corner and a wood post was set for the corner and bearing trees were recorded.

12" Aspen	S 79 E	89 links
12" Bur Oak	S 50 W	137 links

1940's? Roll O-09, of the MN/DOT Highway plans, File No. 30-39 and S.P. 0503, note a 2" X 2" Hub at the intersection of a road north/south and a fence line east/west with the following reference ties:

8" Twin Oak	W	45.3
TP	E	89.9
TP	SW	73.2

The plans also note a distance of 2662.5 feet to the SE corner Sec 14 and a distance of 2665.8 feet to the NE corner Sec 14.

1983 Paul Wollen, LS No. 10461 used corner and notes a distance of 2663.50 feet to the SE corner of Section 14.

1999 On December 17, 1999 William Lunser found a 3/4" pipe at the corner. He filed a Certificate of Location (#283121) and notes a distance of 2661.0 feet to the NE Cor Sec 14 and a distance of 2661.08 feet to the SE Cor Sec 14.

2004 Found 3/4 " iron pipe and measured 2661.15 feet to the NE corner and 2661.07 feet to the SE corner and found the pipe to be 7.95 feet east of a straight line between section corners. No evidence found of GLO BT or old MN/DOT ties.
County Coordinates obtained by GPS to 3/4 " iron pipe:
NAD 83 (1996 Adjustment)
N- 118543.937
E- 505420.863