

**Statement of Evidence:**

**L153**

East Quarter Corner of Section 15, Township 36 North, Range 30 West, Minden Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey established this corner and a wood post was set for the corner and bearing trees were recorded.  
10" Bur Oak                    S 2 E                    944 links

1971 William Lunser, LS No. 9394, set a ½ " iron pipe for the corner by lost method measuring 2679.04 feet to the NE and SE corners of Section 15 and filed a Certificate of Location (Doc. No. 133426). (This is also noted in County Surveyor's Record Book 1, page 189).

1995 Lunser information gives distances of 2679.84 feet to the NE and SE corners.

2004 Danny Kron, LS 42621, found iron pipe. He measured 2679.19 feet to NE corner and 2680.66 feet to the SE corner.  
County Coordinates obtained by traverse by Surveying & Engineering Professionals, Inc.  
NAD 83 (1996 Adjustment)  
N- 118653.667  
E- 500107.135

2004 MN/DOT found iron pipe.  
County Coordinates obtained GPS  
NAD 83 (1996 Adjustment)  
N- 118654.089  
E- 500107.061

2009 MnDot found a ½" iron pipe and established reference ties. (Certificate of Location Doc. No. 368989)

2009 Westwood Professional Services, Inc. found a ½" iron pipe 2678.88 feet from the NE corner and 2680.97 from the SE corner. Coordinate position is in agreement with 2004 locations by Danny Kron, LS 42621 and MN/DOT. Established reference ties.  
County Coordinates obtained GPS  
NAD 83 (1996 Adjustment)  
N- 118653.98  
E- 500107.22