

Statement of Evidence:

L263

East Quarter Corner of Section 26, Township 36 North, Range 30 West, Minden Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at the corner location and bearing trees were recorded.

4" Blk Oak	S 53 1/4 W	74 links
6" Blk Oak	N 21 E	106 links

1967 Milner Carley, LS 855, shows corner on a Certificate of Survey in the SE $\frac{1}{4}$ of the NE $\frac{1}{4}$.

1984 Paul Wollen, LS 10461, found a 3/4" pipe at the corner location. He set a cast iron monument at the centerline of a road north/south and occupation east/west. Filed Certificate of Location (Doc. No. 173392).

1992 County Coordinates from MN/DOT:
NAD 83 (1986 Adjustment)
N-107936.151
E-505579.144

2004 Danny Kron, LS 42621, found CIM. He measured 2638.58 feet to NE corner and 2649.11 feet to the SE corner.
County Coordinates obtained by traverse by Surveying & Engineering Professionals, Inc.
NAD 83 (1996 Adjustment)
N- 107936.443
E- 505578.629

2008 Westwood Professional Services, Inc. found a CIM at centerline of north/south gravel road. Established new reference ties and verified 2004 coordinates and distances.