

East Quarter Corner of Section 34, Township 36 North, Range 30 West, Minden Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

Pre 1940 MN/DOT notes by C. H. West for possible TH 95 alignment show stone monument in place with a distance of 2684.7 feet to the SE corner.

1957 County Surveyor's Record Book 1, page 227, note an Iron pipe over a rock with the following reference ties:  
TP NE 47.3  
PP NW 53.5  
Guy Pole SE 52.15  
(Also noted in Notebook No. 110.)

1971 County Highway ties to a 1 1/2" pipe:  
Brace Pole SE 52.14  
PP SW 47.95  
PP NW 53.61

1992 County Coordinates from MN/DOT to 1" iron pipe:  
NAD 83 (1986 Adjustment)  
N-102689.311  
E-500389.522

1992 Paul Wellen, LS 10461, found a 1" iron and replaced with a cast iron monument and filed a Certificate of Location (#216286).

2000 Plat of THE FAIRWAYS surveyed by Perry Zieske and corner is shown as a CIM.

2003 Westwood Professional Services, Inc. found a 1/2" X 1/2" Iron Pin at the corner and located it using GPS. Pin checks with 3 of Wellen's ties and checks with distance given on the plat of THE FAIRWAYS to the SE corner of Section 34. We measured 2682.16 feet to the NE corner and 2688.45 feet to the SE corner.  
County Coordinates Obtained by GPS (1/2" X 1/2" Pin)  
NAD 83 (1996 Adjustment)  
N-102689.591  
E-500389.051

**NOTE: CORNER SHOULD BE EXCAVATED FOR STONE MONUMENT!**

2003 Westwood Professional Services, Inc. found a 1/2" iron pipe capped 40341. Established reference ties. County Coordinates Obtained by GPS (1/2" X 1/2" Pin)  
NAD 83 (1996 Adjustment)  
N-102689.591  
E-500389.051